



File: E209153



ISO9001:2008 Certified

Mechanical Specifications (mm)

	D:	30.0	±	Max
	T:	8.5	±	Max
	Lead Diameter		±	
	S:	17.1	±	Nom
	L:	21.0	±	Nom
Coating Lead Run Down (straight Leads)		5.0	±	Max
	B:	3.70	±	Nom
	C:	0.80	±	Nom



Electrical Specifications

	Resistance:	10.0 Ω	±	25 %
Max Steady State Current upto 65°C:		15.00		A
Max Rec. Energy Rating:		250		J
Actual Failure Instantaneous Energy:		500		J
Maximum Capacitance @ 120 VAC:		17,500		µf
Maximum Capacitance @ 240 VAC:		4,366		µf
Maximum Capacitance @ 440 VAC:		1,086		µf
Maximum Capacitance @ 680 VAC:		541		µf
Resistance @ 100% Max Current:		0.03		Ω
Resistance @ 50% Max Current:		0.06		Ω
Body Temperature at 100% Max Current:		185.00		°c
Dissipation Constant:		85.2		mw/°c
Thermal Time Constant:		64		Sec.
Material Type (for Beta and Curve):		I		

AS32 10015	
Date: 03/15/2011	Drawn by: Erin Landis
Ametherm, Inc. 3111 N. Deer Run Road Carson City, Nevada USA 89701 www.ametherm.com	Approved By: Mehdi Samii
	Revision: